

# MC65

### Rugged software configurable dual 3.5G WAN Enterprise Digital Assistant (EDA)



## Make the most out of every minute in the field — with the Motorola MC65

Supercharge your mobile workforce and redefine productivity with the toughest, most flexible EDA on the market. Workers have multiple tasks and limited time. With the MC65, they have the tools in hand to get their jobs done right — right now. Desktop-like performance provides instant access to the applications and information back at the office. Shave hours of time out of the work week by capturing and processing just about any type of data on site, quickly and easily — from a single document to hundreds of bar codes, a library of photos or a signature. Activate and reactivate the MC65 on virtually any cellular network in the world, eliminating the need to purchase network technology (GSM or CDMA) specific devices, extending device lifecycle and ensuring that each and every worker has the best connection possible. Add a customizable user interface that makes doing business easier than ever and you have a real workforce multiplier — a device that turns paperwork and repeat visits into more tasks completed per day.

### Streamline and error-proof processes with advanced data capture

The MC65 does it all —1D and 2D bar codes, photos complete with embedded notes, documents, signatures and more. Poorly printed or damaged bar codes a problem? Not for the MC65. Our most advanced scanning technology allows the rapid-fire capture of items as they are removed from the delivery truck, so your customers get what they ordered, every time.

With the MC65, an equipment inspector can capture a photo, add comments and automatically embed a geostamp via integrated GPS, sending supervisors the information they need to get the right technician to the right location to complete a repair. And that repair technician can take and transmit live video to collaborate with a specialist to troubleshoot a problem. A city building inspector can capture a document, complete with legible fine print and a signature, keeping all forms related to a code enforcement case in hand. And when account managers scan the product inventory remaining on the shelves in a grocery store, the resulting real-time count creates real-time accurate sales orders and production schedules.

### Connect to virtually any carrier network in the world — GSM or CDMA

The MC65 offers a Motorola first — the ability to connect to virtually any wireless carrier around the world. Both 3.5G GSM HSPA and CDMA EVDO Rev A software configurable cellular radios are built into the device, allowing you to select the network that will provide the best coverage for your workers. Do your workers travel through large territories best served by different networks? Need to activate on a different network for workers in a different office? No problem. This single device can be deployed and re-deployed on virtually any network, anywhere in the world, making purchasing and device management easy — and maximizing your return on investment.

#### **FEATURES**

#### **HIGH-POWERED PLATFORM**

#### The most advanced mobile operating system

Microsoft's Windows® Mobile® 6.5 increases interoperability with existing enterprise infrastructure; enhances security features; provides a more flexible development platform; improves mobile messaging collaboration

#### Powerful microprocessor designed for mobility

The MSM 7627 @ 600 MHz with multi-processor architecture delivers desktop-like multimedia performance — even on the most demanding applications

#### The memory to support any application

256MB RAM/1GB Flash and a user accessible microSD card slot with support up to 32GB provide the memory space required to enable robust performance for database and other processing intensive applications

#### Protects your application investments

Support for Motorola's Enterprise Mobility Developer Kit (EMDK) APIs preserves existing application investments by enabling easy and cost-effective porting of applications from other Motorola mobile computers

#### **COMPREHENSIVE WIRELESS CONNECTIVITY**

Works on any cellular network

Motorola MAX *FlexWAN* provides true network independence with the industry first software configurable dual 3.5G broadband WAN; supports GSM HSPA and CDMA-EVDO Rev A; deploy and re-deploy a single pool of devices anywhere in the world on virtually any network

#### Works on any wireless LAN

The 802.11a/b/g tri-mode radio connects to both 2.4Ghz and 5Ghz WLANs for cost-effective voice and data connectivity in the office and hot spots; 802.11a support enables segmentation of voice traffic to ensure voice quality

#### The most advanced Bluetooth functionality

Bluetooth® v2.0 with EDR provides a wireless connection to more device types, including modems, printers, headsets and more; simplifies pairing; improves security; reduces power consumption

#### THE MOST RUGGED EDA

Motorola MAX *Rugged* for industry leading rugged design — and reliability



Drop (impact) test: multiple 6 ft./1.8 m drops per MIL-STD 810G

Tumble (endurance) test: reliable operation after 1,000 1.5 ft./0.5 m consecutive tumbles (2,000 drops) in Motorola's tumble drum

IP64 sealing: complete protection against dust and splashing liquids

Patented Monocoque 'unibody' housing: greatly improves structural stability and ability to handle the twisting common in a fall or bump

Patented I/O connector: improves the reliability and durability of the accessory point of interface

Improved shock absorption for internal components: a rigid yet lightweight magnesium frame encases the main circuit board and all electronics

Rugged display construction: space between display and touchscreen helps prevent damage to the display

#### The most rugged EDA design yet - period

The MC65 is built to last, so your workers have a device they can count on while your business enjoys a maximum return on investment (ROI). We designed it with features that ensure reliable operation despite drops and exposure to heat, cold, dust, and moisture. Tested for toughness, the device passes our own stringent drop and tumble tests and meets environmental sealing, military standard (MIL-STD) and IEC specifications. Structural stability has been improved with our patented unibody housing and a special internal component provides extra protection for sensitive electronics. There's even a patented spring-loaded accessory interface that prevents damage if the MC65 is dropped while attached to a peripheral, like a magnetic stripe reader (MSR).

#### Finally — a user interface built for business

Complex devices can leave users struggling to find and access features, instead of focusing on the task at hand. With the Motorola Enterprise User Interface (MEUI), workers can access everything they need to do their job with a tap or two - from business applications to data capture and conference call functions to email and text messages. Either your employees

or IT staff can tailor this unique customizable business-class interface to simplify use, streamlining everyday tasks and improving productivity.

#### Hear every word on every call

Every call counts - whether you're talking to customers, supervisors, co-workers or other business associates. But out in the field, background noise can wreak havoc with phone conversations. The MC65's Dual-Microphone Noise Cancellation technology makes sure that all anyone will hear is you. Our leading-edge noise reduction and echo cancellation technology uses one microphone to capture the speaker's voice and a second to identify and eliminate distracting background noise, including wind, crowds, vehicles or other conversations in the area.

#### Sensor technology that makes good business sense

The MC65 is a new class of device, one that is able to sense its environment and take action to conserve battery power, provide consistent screen visibility and adjust ringer settings. For example, the integrated accelerometer reacts to motion, or the lack of motion. You can automatically switch to portrait or landscape display modes to match the device orientation. The

#### **ADVANCED DATA CAPTURE**

#### 101100 Motorola MAX Data Capture for advanced high-performance multi-mode data capture

Motorola's latest generation 2D imager: delivers unparalleled laserlike performance on both 1D and 2D bar codes; reads even damaged and poor quality codes; omni-directional reading eliminates need to align bar code and scanner window for rapid-fire comfortable scanning

3.2 autofocus flash-enabled digital color camera with user-controllable flash: can capture photos, videos, documents with legible fine print and bar codes (for non-intensive scanning applications)

#### **COMPREHENSIVE VOICE**

#### Motorola MAX Voice delivers advanced voice functionality and voice quality

Leading-edge noise reduction and echo cancellation technology eliminates background noise; high quality speakerphone, microphone and transducer provide robust support for handset, Bluetooth headset and speakerphone modes

#### **ADVANCED USER FEATURES**

#### Industry first business-class interface the Motorola Enterprise User Interface (MEUI)

This customizable business-class interface provides faster and easier access to features and applications; allows users to tailor the interface to improve their unique workflow and maximize on-the-job efficiency

#### Motorola MAX Sensor for the intelligence to sense — and act — on the environment



Motion sensing: automatically rotates screen; powers down when not in use to preserve battery; enables utilization of sensor data in custom applications

Light sensing: automatically adjusts display as workers move between indoors and outdoors to maintain visibility at all times.

Sound sensing: automatically adjust settings based on environmental noise levels — such as reducing ringer volume and activating vibration mode

ٹے

#### Anywhere anytime accurate $\langle \Phi \rangle$ GPS with Motorola MAX Locate

Enables a signal lock in challenging areas such as urban canyons and deep inside buildings where GPS is typically not available; highly precise positioning improves application accuracy; provides users with location-based services in more areas; supports Autonomous and Assisted GPS with gpsOneXTRA™

#### **ADVANCED PHYSICAL FEATURES**

#### Advanced ergonomic design for ease of use and user comfort

Specifically designed for one-handed operation — data entry is easy regardless of hand size with minimal movement

MC65 can also power down to sleep mode when the device is placed face down or remains untouched for a pre-defined period of time. With full access to the accelerometer data, you can create custom business applications that help identify a potential man down, improving the safety of remote field workers. As workers travel from inside buildings to bright sunlight, the display automatically adjusts to save power, ensuring the screen is readable at all times. And when workers enter a noisy or quiet area, ringer volume and vibration mode are automatically adjusted to make sure calls are not missed and co-workers in the vicinity are not disturbed.

#### The Motorola end-to-end advantage

When you choose the MC65, you enjoy the advantages of world-class partners, world-class management solutions and world-class services. Our partners provide a best-in-class broad set of ready-to-go and custom applications that minimize deployment time and cost. Our Mobility Services Platform allows you to manage your entire mobility solution — including Motorola mobile computers and peripherals as well as mobile devices from other manufacturers. And our Service from the Start with Comprehensive Coverage support program is a unique service that protects your investment and keeps your MC65 devices operating at peak performance. This program sets the standard for post-deployment support by including normal wear and tear, as well as coverage for internal and external components damaged through accidental breakage — significantly reducing your unforeseen repair expenses. This truly comprehensive service also covers all the items that ship 'in the box' at no additional charge, including the stylus, screen protector, hand strap and battery door.

For more information on how the MC65 can redefine the productivity of your mobile workforce, please visit us on the web at www.motorola.com/MC65 or access our global contact directory at www.motorola.com/enterprisemobility/contactus

#### Crystal clear text and graphics

Best-in-class 3.5 inch high-resolution color VGA touchscreen display presents extra crisp text, photographs, video and maps in any lighting condition

#### A family of keypads for global flexibility

OWERTY, AZERTY, OWERTZ and Numeric keypads enable the MC65 to support a wide range of applications in just about any geography

#### Compatible with MC55 accessories

Upgrade from the MC55 to the latest mobile technology advancements while preserving your existing accessory investments

#### WIRED NETWORK SECURITY OVER ANY WIRELESS NETWORK

### Make sure only authorized users access your devices, your data and your network

Compatibility with Motorola's Mobile Security Suite provides device-level protection — a firewall, intrusion prevention, enforced authentication, data encryption and integrity monitoring protect the data that is resident on and in transit to and from your MC65 devices; Mobile Virtual Private Networks (MVPNs) bring wired-line security to wireless communications without the typical performance degradation

#### EASY CENTRALIZED MANAGEMENT

### Easy global remote management of your devices — and their accessories

Compatibility with Motorola's Mobility Services Platform (MSP) enables comprehensive and flexible centralized management of Motorola mobile computers and non-Motorola mobile computers and peripherals, anywhere in the world, all from a single console

#### **END-TO-END SUPPORT SERVICES**

### Increase uptime and reduce support costs with all-inclusive support plan

Optional Service from the Start with Comprehensive Coverage covers normal wear and tear as well as internal and external components damaged through accidental breakage for both device and select accessories

### **MC65 Specifications**

Physical Characteristi	CS		
Dimensions:	6.38 in. L x 3.03 in. W x 1.32 in. D (with antenna 162.2 mm L x 77 mm W x 33.5 mm D (with antenn		
Weight:	12.5 oz./359g (with rechargeable 3600mAh Lithium Ion battery)		
Display:	3.5 in. color VGA display, touch, 640 x 480 portrait		
Touch Panel:	Glass analog resistive touch		
Backlight:	LED backlight		
Standard Battery:	Rechargeable Lithium Ion 3.7V, 3600 mAh battery,		
Backup Battery:	Li-Al battery (rechargeable) 25mAh 3.0V (not user-accessible or replaceable)		
Expansion Slot:	microSD slot (supports up to 32GB)		
Communication Interface:	USB 2.0 High Speed (host and client)		
Notification:	Audible tone plus multi-color LEDs		
Keypad Options:	Numeric, QWERTY, AZERTY, QWERTZ		
Audio:	Dual microphone support with noise cancellation vibrate alert; speaker; Bluetooth headset		
Performance Characte	eristics		
CPU:	MSM Qualcomm 7627@ 600 MHz (multi-processor architecture)		
Operating System:	Microsoft® Windows Mobile® 6.5 Professional		
Memory:	256 MB RAM/1 GB Flash		
User Environment			
Interfaces:	Motorola Enterprise UI: customizable homescreen, enhanced dialer and enterprise camera solution		
Operating Temperature:	14° F to 122° F/-10° C to 50° C		
Storage Temperature:	-40° F to 158° F/-40° C to 70° C		
Humidity:	5 to 95% non-condensing		
Drop Specification:	Multiple 6 ft. drops per MIL-STD 810G specifications		
Tumble Specification:	1,000 1.6 ft./0.5 meter tumbles (2,000 drops) at room temperature; per applicable IEC tumble specifications		
Sealing:	IP64; per applicable IEC sealing specifications		
Vibration:	4g's PK Sine (5Hz to 2KHz); 0.04g2/Hz Random (20Hz to 2KHz); 60 minute duration per axis, 3 axis		
Thermal Shock:	-40° F to 158° F/-40° C to 70° C rapid transition		
Electrostatic Discharge (ESD):	± 15kv Air discharge, ± 8kv direct discharge, ± 8kv indirect discharge		

Battery Performance         Standby Time:       100 Hours         Talk Time:       6 Hours         User Profiles:       8 Hours (user profile dependent)         Motorola Interactive Sensor Technology (IST)         Motion Sensor:       3-axis accelerometer that enables motion- sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       Options:         Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera       Resolution:         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)       Focal Distance:         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Skew Tolerance:
Talk Time:       6 Hours         User Profiles:       8 Hours (user profile dependent)         Motorola Interactive Sensor Technology (IST)         Motion Sensor:       3-axis accelerometer that enables motion- sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       Options:         Options:       Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera       Resolution:         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)       Focal Distance:         Focal Distance:       From center of exit window: SR - 7.5 in,/19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal
User Profiles:       8 Hours (user profile dependent)         Motorola Interactive Sensor Technology (IST)         Motion Sensor:       3-axis accelerometer that enables motion- sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       0         Options:       Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera       Resolution:         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)       Focal Distance:         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Motorola Interactive Sensor Technology (IST)         Motion Sensor:       3-axis accelerometer that enables motion- sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       Options:         Options:       Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera       Resolution:         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)       Focal Distance:         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Motion Sensor:       3-axis accelerometer that enables motion-sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       Options:         Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal
sensing applications for dynamic screen orientation and power management         Light Sensor:       Ambient light sensor to auto adjust display backlight brightness         Data Capture       Options:         Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal
backlight brightness           Data Capture           Options:         Two configurations available: 2D imager; 2D imager + 3.2 MP Camera           Data Types:         1D and 2D bar codes, photographs, video, signatures, documents           Camera           Resolution:         3.2 megapixel           Illumination:         User controllable flash           Lens:         Autofocus           2D Imager Engine (SE4500)           Focal Distance:         From center of exit window: SR - 7.5 in./19 cm           Sensor Resolution:         752 x 480 pixels           Field of View:         Horizontal 40°; Vertical 25°           Optical Resolution:         WVGA 752H X 480V pixels (gray scale)           Roll Tolerance:         ± 60° from normal           Skew Tolerance:         ± 60° from normal           Ambient Light         Indoor: 450 ft. candles (4845 lux)
Options:       Two configurations available: 2D imager; 2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera       Resolution:         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
2D imager + 3.2 MP Camera         Data Types:       1D and 2D bar codes, photographs, video, signatures, documents         Camera         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
signatures, documents         Camera         Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Resolution:       3.2 megapixel         Illumination:       User controllable flash         Lens:       Autofocus <b>2D Imager Engine (SE4500)</b> Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Illumination:       User controllable flash         Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Lens:       Autofocus         2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
2D Imager Engine (SE4500)         Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Focal Distance:       From center of exit window: SR - 7.5 in./19 cm         Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Sensor Resolution:       752 x 480 pixels         Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Field of View:       Horizontal 40°; Vertical 25°         Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Optical Resolution:       WVGA 752H X 480V pixels (gray scale)         Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Roll Tolerance:       360°         Pitch Tolerance:       ± 60° from normal         Skew Tolerance:       ± 60° from normal         Ambient Light       Indoor: 450 ft. candles (4845 lux)
Pitch Tolerance:     ± 60° from normal       Skew Tolerance:     ± 60° from normal       Ambient Light     Indoor: 450 ft. candles (4845 lux)
Skew Tolerance:         ± 60° from normal           Ambient Light         Indoor: 450 ft. candles (4845 lux)
Ambient Light Indoor: 450 ft. candles (4845 lux)
5
(from total darkness): Outdoor: 9000 ft. candles (96,900 lux) Sunlight: 8000 ft. candles Fluorescent: 450 ft. candles
Range on 100% UPCA: 16 in./40 cm
Aiming Element (VLD): 655 nm ± 10 nm Laser
Illumination 625 nm ± 5 nm LEDs (2x) Element (LED):
Field of View: Horizontal: 39.6°; Vertical: 25.7°
Voice and Audio
Voice and Audio: VoWWAN; VoWLAN; PTT, VolP-ready; high- quality speakerphone; support for wireless (Bluetooth) headsets; support for PTT headsets, handset and speaker phone modes

#### SPECIFICATION SHEET

MC65

Rugged software configurable dual 3.5G WAN Enterprise Digital Assistant (EDA)

Wireless WAN Voice & Data Communications		Regulatory	
Radio:	Dual 3.5G: GSM HSPA/HSUPA and CDMA EVDO Rev A	Electrical Safety:	IEC/UL/CSA/EN 60950-1
		Environmental:	RoHS/WEEE compliant
Frequency Band:	UMTS/HSDPA and HSUPA: 850, 1900 and 2100 MHz GSM/EDGE: 850, 900, 1800 and 1900 MHz CDMA/EVD0 Rev A: 850 and 1900 MHz	WLAN and Bluetooth (PAN):	USA: FCC Part 15.247, 15.407 Canada: RSS-210 EU: EN 300 328, EN 301 893
Integrated GPS			Japan: ARIB STD-T33, ARIB STD-T66, ARIB
GPS:	Integrated standalone or Assisted-GPS (A-GPS) with gpsOneXTRA™		STD-T70, ARIB STD-T71 Australia: AS/NZS 4268
Wireless LAN Voice and Data Communications		Wireless WAN	<b>Global:</b> 3GPP TS 51.010, 3GPP TS 34.121,
Radio:	Tri-mode IEEE® 802.11a/b/g	(GSM HSUPA/HSPA):	3GPP TS 34.123 GCF and PTCRB approved USA: FCC Part 22, Part 24 Canada: RSS-132, RSS-133 EU: EN301 511, EN301 908 Australia: AS/ACIF S042.1 & 3
Security:	WPA2 (Personal or Enterprise); 802.1x; EAP-TLS; TTLS (CHAP, MS-CHAP, MS-CHAPv2, PAP or MD5); PEAP (TLS, MSCHAPv2, EAP-GTC); LEAP, EAP-FAST (TLS, MS-CHAPv2, EAP-GTC)		
Data Rates Supported:	1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps	Wireless WAN (CDMA-EVDO Rev A):	USA: FCC Part 22, Part 24
Voice Communication:	Voice-over-IP ready, Wi-Fi™-certified, IEEE		Canada: RSS-132, RSS-133
	802.11a/b/g direct sequence wireless LAN, Wi-Fi Multimedia™ (WMM and WMM-PS) Motorola Voice Quality Manager (VQM), Motorola TEAM Express Ready	RF Exposure:	USA: FCC Part 2, FCC OET Bulletin 65 Supplement C Canada: RSS-102 EU: EN 50360; EN 62311 Australia: Radio communications Standard 2003
Wireless PAN Data and Voice Communications		EMI/RFI:	USA: FCC Part 15, Class B
Bluetooth:	Class II, v2.0 with Enhanced Data Rate (EDR)		Canada: ICES 003 Class B EU: EN55022 Class B, EN 55024, EN 301 489-1,
Peripherals and Accessories*			EN 301 489-3, EN 301 489-7, EN 301 489-17, El
Communication and Charging Cables:	Charge only cable, auto charge cable, USB charge/sync cable		301 489-24, EN 60601-1-2, EN 50121-3-2, EN 50121-4
Battery Chargers/ Cradles:	<ul> <li>4-slot battery charger; 4-slot Ethernet cradle;</li> <li>4-slot charge only cradle; single slot USB cradle;</li> <li>vehicle holder using auto charge cable; vehicle</li> <li>cradle with charging capabilities</li> </ul>		Australia: AS/NZS CISPRA-22
		Laser Safety:	IEC Class2 / FDA Class II in accordance with IEC60825-1/EN60825-1
		Warranty	
Vertical Specific Attachments:	Snap-on magnetic stripe reader (MSR); snap-on trigger handle	The MC65 is warranted against defects in workmanship and materials for a period of 12 months from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions	
Soft Goods:	Rigid and soft case holsters, headsets		
* Visit www.motorola.com/m		Recommended Servio	ces

Customer Services: Service from the Start with Comprehensive Coverage





Sensor

Rugged



Data Capture



Locate









motorola.com

Part number SS-MC65. Printed in USA 08/10. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2010 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.