






CW408

Compact, Versatile, User-Friendly

Take your business to the next level with our next-generation compact and easy-to-use label printer



Industry

-  Retail
-  Amusement
-  Travel & Leisure
-  Hospitality
-  Government

Applications

- Ticketing
- Coupon Printing
- Retail Labeling
- Shelf Labeling
- Shipping & Receiving
- Inventory Labeling
- Postal & Mailing

Enhance your business performance by leveraging on our compact **CW408** printer that is designed to fulfill your ticketing and labeling needs.



Features

Automatic paper feed – Zero label wastage!

The automatic paper feed function allows you to easily load labels without opening the cover and enables printing from the first label thus preventing label wastage. Maintenance is also simple as the printer cover opens wide thus allowing you to easily clean the thermal head and platen roller.

Easy to install, compact design

Compared to conventional compact 4-inch printers, the CW408 takes up approximately 30% less space and is ideal for integrated applications and usage at narrow spaces such as temporary reception areas, exhibition areas, ticketing, kiosks etc.

Equipped with organic Electroluminescent (EL) display – Easy to read even in the dark!

As one of the first 4-inch label printers to be equipped with the organic EL display, letters can be read clearly on the screen, even in dark places. The scrolling text display also allows for easy reading of operating instructions.

General Specifications		
Printer Model		CW408
Printing Specifications		
Print Method		Direct Thermal
Print Resolution		8 dots/mm (203 dpi)
Max. Print Speed		Up to 152.4 mm/sec (6 ips)
Max. Printable Area		400mm (L) x 104mm (W) / 15.7" (L) x 4.1" (W)
Hardware Specifications		
CPU		32-bit RISC CPU 125MHz
Memory		Flash ROM: 8MB SDRAM: 64MB
Interface		USB, LAN
Physical Dimensions		178mm (W) x 112mm (D) x 146mm (H) / 7.0" (W) x 4.4" (D) x 5.7" (H)
Weight		1.5kg (Excluding media and options)
Electrical Requirements		Input voltage: AC 100 – 240V ±10% Frequency: 50Hz / 60Hz
Regulatory Approvals		CE
Environmental Requirements		Operating environment: 0 to 40°C / 30 to 80% RH (Non-condensing) Storage environment: -5 to 60°C / 30 to 90% RH (Non-condensing)
Consumables Specifications		
Media Type		Direct thermal media – Roll (using unwinder option), fan-fold or single
Media Size	Continuous	Length: 25 to 397mm (Liner: 28 to 400mm) Width: 25 to 115mm (Liner: 28 to 118mm)
	Tear-Off	Length: 25 to 397mm (Liner: 28 to 400mm) Width: 25 to 115mm (Liner: 28 to 118mm)
	Cutter	Length: 25 to 397mm (Liner: 28 to 400mm) Width: 25 to 115mm (Liner: 28 to 118mm)
	Dispenser	Length: 25 to 100mm (Liner: 28 to 103mm) Width: 25 to 115mm (Liner: 28 to 118mm)
	Single label	Length: 127 to 397mm (Liner: 130 to 400mm) Width: 25 to 115mm (Liner: 28 to 118mm)
Max. Label Roll Diameter		115mm / 4.5"
Label Roll Core Diameter		40mm / 1.6"
Media Thickness		0.08 ~ 0.21mm / 0.0031" ~ 0.0083" Using cutter: 0.08 ~ 0.12mm / 0.0031" ~ 0.0047"
Max. Folding Height for Fanfold Media		100mm / 3.93"
Media Sensor		I-Mark sensor (Reflective type), Gap sensor (Transmissive type), Label positioning sensor (Reflective sensor)
Fonts/Barcode Specifications		
Fonts		Bitmap Font: OCR-A, OCR-B, XU, XS, XM, XB, XL, Simplified Chinese GB18030 – 16x16 dots (Mincho) and 24x24 dots (Gothic) Outline Font: Alphanumeric, Symbols
Rotation		Characters: 0°, 90°, 180°, 270° Barcode: Parallel 1 (0°), Parallel 2 (180°), Serial 1 (90°), Serial 2 (270°)
1D Barcode		UPC-A/E, JAN/EAN, CODE 39/93/128, UCC/EAN 128, ISBT128, CODABAR (NW-7), ITF, Industrial 2 of 5, Matrix 2 of 5, MSI, UPC add-on code, POSTNET, GS1 DataBar Omnidirectional/Truncated/Stacked/Stacked Omnidirectional/Limited/Expanded/Expanded Stacked, Composite Symbols
2D Barcode		QR Code (including Micro QR), Security QR Code, PDF417 (including MicroPDF), MaxiCode, GS1 DataMatrix, DataMatrix (ECC200)
Options		
Cutter, Dispenser, Unwinder		

OUR PRESENCE IN ASIA PACIFIC

HEADQUARTERS
SATO Corporation
1-7-1 Shimomeguro, Meguro-ku, Tokyo
153-0064, Japan
TEL: +81 3 6665 0600
www.satoworldwide.com

SATO International Asia Pacific Pte Ltd
483B, Alexandra Road,
Alexandra Technopark, #09-01/02,
Singapore 119968
TEL: +65 6271 5300
www.satoasiapacific.com

OFFICES
[Australia](#)
SATO Australia Pty Ltd
TEL: +61 3 8814 5330
www.satoaustralia.com

[China \(PRC\)](#)
SATO Shanghai Co. Ltd
TEL: +86 21 3252 2777
www.satochina.com

[India](#)
SATO Auto-ID India Private Limited
TEL: +91 124 4498555
www.satoindia.com

[Indonesia](#)
PT. SATO Nagatomi
TEL: +62 21 652 2752
www.satonagatomi.com

[Malaysia](#)
SATO Auto-ID Malaysia Sdn Bhd
TEL: +60 3 7620 8901
malaysia.satoworldwide.com

[New Zealand](#)
SATO New Zealand Ltd
TEL: +64 9 477 2222
www.satonewzealand.com

[Singapore](#)
SATO Asia Pacific Pte Ltd
TEL: +65 6271 5300
www.satoasiapacific.com/singapore

[Thailand](#)
SATO Auto-ID (Thailand) Co., Ltd
TEL: +66 2 736 4460
www.satothailand.co.th/

[Vietnam](#)
SATO Vietnam Solutions Co. Ltd
TEL: +84-08-3910 1350/1
www.satovietnam.com

REPRESENTATIVE OFFICE
[Korea](#)
SATO Asia Pacific Pte Ltd
Korea Representative Office
TEL: +82 2 761 5072
www.satokorea.com

For more information about SATO in the region, visit www.satoasiapacific.com

©2013 SATO Corporation. All rights reserved.
Specifications subject to change without notice. Any unauthorized reproduction of the contents of this presentation, in part or whole, is strictly prohibited.
SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.